



YINKE VALVE
FLOW CONTROL

Class 2500 Cast Steel Gate Valve

Class 2500 Cast Steel Gate Valve is configured for very high-pressure critical isolation. Available materials, end connections, operation and inspection options can be matched to the project specification.

Technical Specification

Pressure Class	ASME Class 2500
Design Standard	API 600 / ASME B16.34
Size Range	2-48 in
Body Materials	WCB, WCC, LCB, LCC, CF8M, WC6, WC9
Connections	RF, RTJ, BW
Application Focus	Full-bore isolation in refinery, pipeline, petrochemical and power piping

Selection Notes

Class 2500 is used for very high-pressure critical isolation. Requires the most disciplined rfq package in this structure; incomplete service data can lead to major design changes. For this valve design, buyers should also review wedge, stem, bonnet and seat design.

Materials

Typical project materials include WCB, WCC, LCB, LCC, CF8M, WC6, WC9. The correct grade depends on corrosion, minimum and maximum design temperature, toughness, hardness limits and the project material specification.

End Connections

Rtj or bw are commonly considered, but the project piping class is the governing document. Available connection families for this product include RF, RTJ, BW.

Testing & Documentation

Define nde, material verification, pressure-test acceptance, documentation and witness points in the itp before production.

RFQ Information

• Valve type and nominal size	• Pressure class / rating
• Body and trim material	• End connection / facing
• Operation or actuator	• Service fluid and design temperature
• Quantity and delivery requirement	• Inspection, testing and document requirements

For quotation, send the valve list, datasheet or project specification together with the required quantity and delivery location.