



YINKE VALVE
FLOW CONTROL

Eccentric Plug Valves

Eccentric Plug Valves are configured for wastewater, slurry and process isolation requiring low seat rubbing. Buyers can compare pressure class, size, materials, end connections and operation, then match the valve to the piping class and service conditions.

Technical Specification

Design Standard	ASME B16.34 / project specification
Size Range	2-24 in
Pressure Classes	Class 150, Class 300, Class 600
Body Materials	Ductile Iron, WCB, CF8M
End Connections	RF, Mechanical Joint
Operation	Manual, gear or actuated where applicable

Selection Notes

Start with the piping class and service conditions, then review plug geometry, lubrication/sleeve system, pressure balancing and port arrangement. For quotation, include plug design, port arrangement, lubrication/sleeve, material, end connection and operating method.

Materials

Typical project material options include Ductile Iron, WCB, CF8M. Final material selection should follow corrosion conditions, design temperature, toughness requirements and the approved material specification.

End Connections

Available connection families include RF, Mechanical Joint. The final facing or weld preparation must match the piping class and approved drawing.

Testing & Documentation

Confirm the required pressure test standard, material certificates, PMI or NDE scope, dimensional inspection, coating records and final document package before production.

RFQ Information

• Valve type and nominal size	• Pressure class / rating
• Body and trim material	• End connection / facing
• Operation or actuator	• Service fluid and design temperature
• Quantity and delivery requirement	• Inspection, testing and document requirements

For quotation, send the valve list, datasheet or project specification together with the required quantity and delivery location.