



YINKE VALVE
FLOW CONTROL

Non-Lubricated Plug Valves

Non-Lubricated Plug Valves are configured for clean process media where reduced maintenance is preferred. Buyers can compare pressure class, size, materials, end connections and operation, then match the valve to the piping class and service conditions.

Technical Specification

Design Standard	API 599 / ASME B16.34
Size Range	2-24 in
Pressure Classes	Class 150, Class 300, Class 600
Body Materials	WCB, LCC, CF8M
End Connections	RF, BW
Operation	Manual, gear or actuated where applicable

Selection Notes

Start with the piping class and service conditions, then review plug geometry, lubrication/sleeve system, pressure balancing and port arrangement. For quotation, include plug design, port arrangement, lubrication/sleeve, material, end connection and operating method.

Materials

Typical project material options include WCB, LCC, CF8M. Final material selection should follow corrosion conditions, design temperature, toughness requirements and the approved material specification.

End Connections

Available connection families include RF, BW. The final facing or weld preparation must match the piping class and approved drawing.

Testing & Documentation

Confirm the required pressure test standard, material certificates, PMI or NDE scope, dimensional inspection, coating records and final document package before production.

RFQ Information

• Valve type and nominal size	• Pressure class / rating
• Body and trim material	• End connection / facing
• Operation or actuator	• Service fluid and design temperature
• Quantity and delivery requirement	• Inspection, testing and document requirements

For quotation, send the valve list, datasheet or project specification together with the required quantity and delivery location.